

[Get a Quote](#)

Overview

The Cisco ASA 5540 Adaptive Security Appliance ASA5540-BUN-K9 delivers high-performance, high-density security services with Active/Active high availability and Gigabit Ethernet connectivity for medium-sized and large enterprise and service-provider networks, in a reliable, modular appliance. With four Gigabit Ethernet interfaces and support for up to 100 VLANs, businesses can use the Cisco ASA 5540 to segment their network into numerous zones for improved security. The Cisco ASA 5540 Adaptive Security Appliance scales with businesses as their network security requirements grow, delivering exceptional investment protection and services scalability. The advanced network and application-layer security services and content security defenses provided by the Cisco ASA 5540 Adaptive Security Appliance can be extended by deploying the AIP SSM for high-performance intrusion prevention and worm mitigation.

Quick Spec

Figure 1 shows the appearance of ASA5540-BUN-K9.



Table 1 shows the quick spec.

Product Code	ASA5540-BUN-K9
Product Description	Cisco ASA 5540 Firewall Edition includes 4 Gigabit Ethernet interfaces + 1 Fast Ethernet interface, 5000 IPsec VPN peers, 2 SSL VPN peers, 3DES/AES license
Users/Nodes	Unlimited
Firewall Throughput	Up to 650 Mbps
Maximum Firewall and IPS Throughput	<ul style="list-style-type: none"> Up to 500 Mbps with AIP-SSM-20 Up to 650 Mbps with AIP-SSM-40
Memory	1 GB
Minimum System Flash	64 MB
Dimensions (H x W x D)	1.75 x 17.5 x 14.25 in. (4.45 x 20.04 x 36.20 cm)
Weight (with Power Supply)	20.0 lb (9.07 kg)

Compare to Similar Items

Table 2 shows the comparison between ASA5540-BUN-K9 and ASA5505-BUN-K9.

Product Code	ASA5540-BUN-K9	ASA5505-BUN-K9
Product Description	Cisco ASA 5540 Firewall Edition includes 4 Gigabit Ethernet interfaces + 1 Fast Ethernet interface, 5000 IPsec VPN peers, 2 SSL VPN peers, 3DES/AES license	ASA 5505 Security Appliance with SW, 10 Users, 8 ports, 3DES/AES, Cisco ASA 5500 Series Firewall Edition Bundles
Users/Nodes	Unlimited	10
Firewall Throughput	Up to 650 Mbps	Up to 150 Mbps
Maximum Firewall and IPS Throughput	<ul style="list-style-type: none"> ● Up to 500 Mbps with AIP-SSM-20 ● Up to 650 Mbps with AIP-SSM-40 	<ul style="list-style-type: none"> ● Up to 150 Mbps with AIP-SSC-5
Memory	1 GB	256 MB
Minimum System Flash	64 MB	64 MB
Dimensions (H x W x D)	1.75 x 17.5 x 14.25 in. (4.45 x 20.04 x 36.20 cm)	1.75 x 7.89 x 6.87 in. (4.45 x 20.04 x 17.45 cm)
Weight (with Power Supply)	20.0 lb (9.07 kg)	4.0 lb (1.8 kg)

Get more information

Do you have any question about the ASA5540-BUN-K9?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

ASA5540-BUN-K9 Specification	
Product Number	ASA5540-BUN-K9
Product Description	Cisco ASA 5540 Firewall Edition includes 4 Gigabit Ethernet interfaces + 1 Fast Ethernet interface, 5000 IPsec VPN peers, 2 SSL VPN peers, 3DES/AES license
Users/Nodes	Unlimited
Firewall Throughput	Up to 650 Mbps
Maximum Firewall and IPS Throughput	<ul style="list-style-type: none"> ● Up to 500 Mbps with AIP-SSM-20 ● Up to 650 Mbps with AIP-SSM-40
3DES/AES VPN Throughput	Up to 325 Mbps
IPsec VPN Peers	5000
SSL VPN Peers Included/ Maximum)	2/2500
Concurrent Connections	400,000
New Connections/ Second	25,000
Integrated Network Ports	4 Gigabit Ethernet, 1 Fast Ethernet
Virtual Interfaces (VLANs)	200
Security Contexts (Included/ Maximum)	2/50
High Availability	Active/Active and Active/ Standby
Expansion Slot	1, SSM
User-Accessible Flash Slot	1

USB 2.0 Ports	2
Serial Ports	2 RJ-45, console and auxiliary
Rack-Mountable	Yes
Wall-Mountable	Not Available
Security Lock Slot (for Physical Security)	Not Available
Memory	1 GB
Minimum System Flash	64 MB
System Bus	Multibus architecture
Form Factor	1 RU, 19-in. rack-mountable
Dimensions (H x W x D)	1.75 x 17.5 x 14.25 in. (4.45 x 20.04 x 36.20 cm)
Weight (with Power Supply)	20.0 lb (9.07 kg)
Safety	UL 60950, CSA C22.2 No. 60950, EN 60950 IEC 60950, AS/NZS60950
Electromagnetic Compatibility (EMC)	CE marking, FCC Part 15 Class A, AS/NZS CISPR22 Class A, VCCI Class A, EN55022 Class A, CISPR22 Class A, EN61000-3-2, EN61000-3-3
Industry Certifications	Common Criteria EAL4 US DoD Application-Level Firewall for Medium-Robustness Environments, Common Criteria EAL2 for IPS on AIP SSM-10 and -20, FIPS 140-2 Level 2, and NEBS Level 3. In process: Common Criteria EAL4+ US DoD Application-Level Firewall for Medium-Robustness Environments, and Common Criteria EAL4 for IPsec/SSL VPN

Want to Buy

[Order Now](#)
[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com